



PRIZOR VIZTECH LIMITED

4G-30AIDSPT-SD-CW

4G 3MP IP SOLAR DUAL
LENS PT CAMERA

4G PT CAMERA WITH SOLAR PANEL



KEY FEATURES

- ◆ 3MP HD IMAGE, ENJOY CLEAR AND CRYSTAL PICTURE QUALITY
- ◆ TOTALLY WIRE-FREE: NO POWER CABLE, NO NETWORK CABLE
- ◆ 2.8 INCH BALL BODY, ENGINEERING PLASTIC MATERIAL, OUTDOOR RAINPROOF, STYLISH, BEAUTIFUL AND EXQUISITE
- ◆ THE MAXIMUM HORIZONTAL ROTATION FOR 263 DEGREES, THE MAXIMUM VERTICAL ROTATION FOR 90 DEGREES
- ◆ 4G CONNECTION & SCAN THE QR CODE ON THE CAMERA TO EASILY CONNECT THE CAMERA
- ◆ WITH ITS OWN HOTSPOT CONNECTION, YOU CAN VIEW THE VIDEO WITHOUT NETWORK
- ◆ SUPPORT CLOUD STORAGE AND LOCAL TF CARD
- ◆ SUPPORT MIC AND SPEAKER, SUPPORT TWO-WAY AUDIO
- ◆ COMES WITH INFRARED LIGHT AND SPOTLIGHT, SUPPORT BLACK AND WHITE AND FULL COLOR MODE
- ◆ ACTIVE DEFENSE, SOMEONE BREAKS INTO THE ALERT AREA, CAMERA PUSHES ALARM INFORMATION IN REAL TIME
- ◆ SUPPORT REMOTE MONITORING BY MOBILE PHONE, YOU CAN VIEW THE LIVE VIDEO ANYTIME ANYWHERE
- ◆ IP66 WATERPROOF RATING, 4000V LIGHTNING PROTECTION
- ◆ INSTALLATION METHODS: POLE INSTALLATION, WALL INSTALLATION AND CEILING INSTALLATION
- ◆ BUILT-IN SIREN. SIREN WILL BE TRIGGER WHEN HUMAN MOVEMENT IS DETECTED. THE VOICE OF THE SIREN CAN BE CUSTOMIZED.
- ◆ BUILT-IN PIR SENSOR
- ◆ BUILT-IN BATTERY 18000MAH RECHARGEABLE LITHIUM BATTERY, WITH 7W SOLAR PANEL
- ◆ 48H BATTERY BACKUP
- ◆ UNIQUE WITH ALL-TIME-COLOR VISION
- ◆ SUPPORT MICRO SD CARD UP TO 256GB



SPECIFICATIONS

MODEL	4G-30AIDSPT-SD-CW
Image Sensor	1/3" CMOS SENSOR
Lens	4MM
Resolution	3MP DUAL LENS
Effective Pixels	2304(H)*1296(V)
TV System	PAL/NTSC
Usable Illumination	Color: 0.01Lux,black and white:0.001 Lux
Sync System	EXTERNAL
Pan and tilt angle	Pan 0 ° 350 ° Tilt 0 ° 180 °
Video stream	Main stream:2304*1296; Sub-stream:640*360
Frame rate	15fps
Image compression	H.264/H.265
Audio format	AAC/G711A
Storage Interface	Support SD card (maximum 256G)
Audio function	Two-way audio(built-in speaker, microphone)
4G Frequency band	FDD-LTE:B1/B3/B5/B8; TDD-LTE:B34/B38/B39/B40/B41;
Solar Panel	7W
Alarm function	Motion detection alarm,and push alarm info
Cloud storage	Support(OPTIONAL)
Working temperature and humidity	-20°C~50°C, Humidity is less than 95% (non-condensing)
IR/LED	IR+ white light (Dome 18 double wick lights + bullet 6 double wick lights)
Infrared distance	20-30 meters & White light-15-20 meters
Power supply	Built-In Rechargeable 18000mAh Battery(48H BACKUP)
Power consumption	≤15W
Dimension	139*215*177mm (WxHxL)

