

PRIZOR VIZTECH LIMITED

PRIZ-22FHD-M



KEY FEATURES

- ◆ HD: 1920 * 1080 HIGHER RESOLUTION THAN ORDINARY MONITORS
- ◆ AUTOMATICALLY DETECT THE RESOLUTION OF THE INPUT SIGNAL AT THE BOTTOM LEFT OF THE SCREEN WHEN STARTING UP, AND THE DEFINITION SPEAKS WITH DATA
- ◆ CLARITY: DELICATE AND LIFELIKE, CONVEYING TRUE COLORS, SHOWING TRUE COLORS
- BRIGHT: IMAGE QUALITY IS IMPROVED, ONLY FOR BETTER PRESENTATION
- ◆ INDUSTRIAL SCREEN, HIGH BRIGHTNESS, HIGH CONTRAST
- ADOPT HIGH-PRECISION STANDARD REGULATED POWER SUPPLY, SPECIALLY DESIGNED FOR INDUSTRIAL EQUIPMENT, SUPPORT 24 HOURS × 365 DAYS UNINTERRUPTED WORK
- ◆ USING 10 BIT IMAGE CHIP PROCESSING TECHNOLOGY, HIGH-PIXEL PROGRESSIVE SCANNING, FINE AND LIFELIKE PICTURE QUALITY
- ◆ SUPPORT INTELLIGENT 3D NOISE REDUCTION, AFTERIMAGE ELIMINATION FUNCTION, DYNAMIC BRIGHTNESS, CONTRAST COLOR OPTIMIZATION TECHNOLOGY
- ◆ APPLY THE WORLD'S LEADING LIQUID CRYSTAL DRIVE SCHEME TO ACCURATELY RESTORE THE FRONT-END SIGNAL, WITH A STRONG SENSE OF REALITY
- ◆ LIQUID CRYSTAL HAS SMALL SIZE, LOW ENERGY CONSUMPTION, ZERO RADIATION, STABLE IMAGE, NO IMPACT ON EYES, NATURAL AND HEALTHY
- ◆ 5 MS EXTREMELY FAST RESPONSE, AVOIDING IMAGE SMEARING DURING HIGH-SPEED OPERATION
- ♦ USING NANOTECHNOLOGY, THE PICTURE IS MORE THREE-DIMENSIONAL AND TRANSPARENT

















PRIZ-22FHD-M

PRIZOR VIZTECH LIMITED

SPECIFICATIONS

MODEL	PRIZ-22FHD-M
Display	
Screen size	22 inch
Resolution	1920*1080 (compatible with 3840*2160/30HZ)
Display ratio	16:9
Brightness	250cd/m² (center point, typical value)
Contrast	1000:1
Viewing angle	160°/170°
Response time	5ms(Gray To Gray)
Color depth	16.7M
Function Attributes	
control method	panel
interface	
power input	12V/3A
input interface	HDMI/VGA/ USB/ CVBS/Audio input/
Output Interface	Audio output
Power consumption	
whole machinePower consumption	28W
Structure	
color	black body
material	flame retardant plastic
Dimensions	503*330*48mm, not including foot height 75mm









PRIZ-22FHD-M

PRIZOR VIZTECH LIMITED

SPECIFICATIONS

MODEL	PRIZ-22FHD-M
Package Size	550*338*105mm
Installation Method	Base, Vesa (100mm*100mm)
Net/Gross Weight	3.7kg/4.6kg
Package Size	550*338*105mm
Installation Method	Base, Vesa(100mm*100mm)
Net/Gross Weight	3.7kg/4.6kg
Operation Environmen	nt
Temperature	Most Suitable For 20°C
Humidity	10%-90%rh
Attachment List	
DC Power Supply, War PA4*12MM (One Bag	rranty Card, Manual, HDMI Cable, Base, Self-tapping Screws)











