



PRIZOR VIZTECH LIMITED



RP-24HDB20-MIR-CW
2.4 MP HD COLOR VIEW
METAL BULLET CAMERA

KEY FEATURES

- ◆ 1/2.9" SONY CMOS SENSOR
- ◆ FULL COLOR VIEW IN NIGHT VISION
- ◆ WDR; WITH IR-CUT
- ◆ WATER RESISTANCE: IP66
- ◆ 2.4MP HD LENS 3.6MM WITH IR-CUT
- ◆ 3600K SOFT WARM LIGHT:2PCS
- ◆ IR RANGE: UP TO 20M
- ◆ SUPPORT LOW ILLUMINATION ,WARM LIGHT DAY/NIGHT FULL COLOR

PRIME SERIES

2.4MP

3DNR



SPECIFICATIONS

MODEL	RP-24HDB20-MIR-CW
IMAGE SENSOR	1/2.9 SONY CMOS SENSOR
MAIN PROCESSOR	SONY
RESOLUTION	2.4MP
EFFECTIVE PIXELS	1920(H)*1080(V)
TV SYSTEM	PAL/NTSC
VIDEO INPUT	AHD/TVI/CVI & CVBS
SYNC SYSTEM	EXTERNAL
USABLE ILLUMINATION	0.1LUX@(F2.1 AGC ON) ; 0LUX WITH IR
S/N RATIO	≥52DB
SCANNING SYSTEM	PROGRESSIVE
VIDEO OUTPUT	NETWORK
LENS	
FOCUS LENGTH	3.6MM
FOCUS CONTROL	FIXED
TYPE	HD IR CORRECTED LENS
PIXEL	3MP
WARM LED	2PCS(COLOR-0.1LUXAGC ON & 0LUX IR ON)
INFRARED DISTANCE	UP TO 20M
IR POWER ON	CDS AUTO CONTROL
IR STATUS	UNDER 10 LUX BY CDS
IR LED	2PCS 3600K SOFT WARM LIGHT
ICR	SUPPORT ICR EXT/COLOR/BW





RP-24HDB20-MIR-CW
2.4 MP HD COLOR VIEW
METAL BULLET CAMERA

PRIZOR VIZTECH LIMITED

SPECIFICATIONS

MODEL	RP-24HDB20-MIR-CW
LANGUAGE	ENGLISH, BULGARIAN, POLISH, FARSI, GERMAN, RUSSIAN, FRENCH, KOREAN, PORTUGUESE, JAPANESE, TURKISH, SPANISH, HEBREW, ITALIAN
HOUSING & DIMENSION	METAL BODY 73MM * 73MM * 190, IP66
OPERATION TEMPERATURE	-20°C ~ +60°C RH95% MAX
STORAGE TEMPERATURE	-20°C ~ +60°C RH95% MAX
POWER SOURCE	DC12V±10%, 1000MA
WEIGHT	500G

