



PRIZOR VIZTECH LIMITED



## RP-HDV0401-5M-PRO

4CH H.265 DVR

### KEY FEATURES

- ◆ 5 IN 1 HYBRID, SUPPORT HDTVI, AHD, CVI,
- ◆ SUPPORT H.265 ENCODING TECHNOLOGY, THE AVERAGE ENCODING EFFICIENCY IS INCREASED BY 50%, AND THE VIDEO STORAGE TIME IS LONGER
- ◆ ANALOG, NETWORK FIVE SIGNAL ACCESS
- ◆ THE TRANSMISSION DISTANCE OF ANALOG COAXIAL CABLE CAN REACH 600M,
- ◆ AND THE VIDEO TRANSMISSION IS RELIABLE
- ◆ SUPPORT UTC FUNCTION, DIRECTLY SET THE CAMERA THROUGH COAXIAL CABLE
- ◆ SUPPORT ONVIF PROTOCOL TO ENSURE THE INTERCONNECTION WITH THE NETWORK CAMERA
- ◆ SUPPORT MOBILE PHONE MONITORING, SUPPORT CLOUD SERVICE,
- ◆ REALIZE APP PREVIEW + REMOTE VIDEO PLAYBACK
- ◆ MOBILE APP-PRIZORPRO
- ◆ COXIAL AUDIO CAMERA SUPPORTED TVI MODE ONLY

### PRIME SERIES



## SPECIFICATIONS

MODEL/NAME		RP-HDV0401-5M-PRO
VIDEO INPUT	VIDEO INPUT	4CH
	COAXIAL HD INPUT	720P/960H@25FPS/1080P@13FPS/4MP@12FPS/5MP@6FPS
	NETWORK VIDEO INPUT	4CH 720P/960P/1080P
	NETWORK VIDEO ACCESS BANDWIDTH	70MBPS
	AUDIO INPUT	1 CH,RCA
AUDIO AND VIDEO OUTPUT	HDMI OUTPUT	1 CH, HDMI INTERFACE; RESOLUTION , 1920X1080P/60HZ;
	VGA OUTPUT	1 CH, VGA INTERFACE, RESOLUTION , 1920X1080P/60HZ
	AUDIO OUTPUT	RCA AUDIO OUTPUT*1, HDMI AUDIO OUTPUT
	CVBS OUTPUT	NA
VIDEO AND AUDIO CODEC SPEC.	VIDEO COMPRESSION STANDARD	STANDARD H.265, H.264
	PLAYBACK	DVR MODE: 2-CH 5MP -H PLAYBACK/4CH 1080P PLAYBACK; NVR MODE: 2-CH 2MP PLAYBACK; 4-CH 2MP PLAYBACK;
	ANALOG VIDEO ENCODING RESOLUTION	5MP-H/(1280*1952)@6FPS;4MP-H(1280*1440)@8FPS; 1080P-H(960*1080)/720P@25FPS; 960H@25FPS
	ANALOG VIDEO CODING RATE	64 KBPS ~2MBPS
	STREAM TYPE	AUDIO AND VIDEO STREAMING / VIDEO STREAMING, SUPPORT VBR / CBR
	AUDIO COMPRESSION STANDARD	G.711(COAXIAL AUDIO ALSO SUPPORT)



## SPECIFICATIONS

<b>RECORDING MANAGEMENT</b>	RECORDING MODE	TIMING , MOTION DETECTION , ALARM
	PLAYBACK MODE	REGULAR PLAYBACK
	BACKUP MODE	USB BACKUP AND NETWORK BACKUP, BACKUP BY TIME
<b>HDD</b>	STORAGE TYPE	SUPPORT 1 SATA INTERFACE
	STORAGE CAPACITY	EACH INTERFACE SUPPORTS A HARD DISK WITH A MAXIMUM CAPACITY OF 6TB
<b>EXTERNAL INTERFACE</b>	NETWORK INTERFACE	1 RJ45 100M ADAPTIVE ETHERNET PORT
	USB INTERFACE	2 USB2.0 PORTS
	ALARM INTERFACE	NA
<b>NETWORK</b>	NETWORK PROTOCOLS	NTP, SMTP, PPPOE, DHCP
<b>OTHERS</b>	POWER INPUT	DC 12 V & 2.5AMP
	POWER CONSUMPTION (WITHOUT HDD)	≤15W
	OPERATING TEMP.	-10°C--+ 55°C
	OPERATING HUMIDITY	10% --90%
	SIZE	2.58*21*4.2CM
	WEIGHT (WITHOUT HDD)	≤1KG

